



MIGHTY LUBE SYSTEMATIC LUBRICATION, INC.

Fremont, Michigan

TECHNICAL DATA SHEET TYPE CSM-2 LUBRICANT

Mighty Lube Type CSM-2 Lubricant is a heavy duty, anti-wear lubricant, which have been formulated to withstand the most extreme industrial conveyor applications.

The use of the Mighty Lube Systematic Lubrication will result in a conveyor system that is protected against wear and corrosion over temperature ranges of 450°F with limited protection up to 1250°F.

Mighty Lube Type CSM-2 Lubricant is formulated with specialty chemicals to exceed the characteristics of an excellent lubricant. Type CSM-2 Lubricant consist of a solvent which acts as a carrier, cleaner and penetrant providing a pathway for the other components to work their way into the wear points. Graphite and synthetic fluids act as the base for the lubricant. This provides a thin film with anti-wear, extreme pressure and temperature protection.

Mighty Lube Type CSM-2 Lubricant and Mighty Lube Lubricating Equipment are the result of years of development dedicated to providing the industry with the highest quality systematic approach to protection against conveyor wear, corrosion, waste and downtime.

TYPICAL SPECIFICATIONS:

Viscosity SUS @100°F	45
Pour Point °F.	-55
Flash Point °F.	240
Color	Black
Viscosity Index	140
Lubricant Solids (suspension)	Colloidal Graphite
Rust Preventive Properties (ASTM D665A) Test	No Corrosion

Mfg. by Mighty Lube Systematic Lubrication, Inc., Fremont, MI 49412
231-924-6160

9569 West 40th Street
Fremont, Michigan 49412

fax: 231.924.6810
email: info@mightylube.com

telephone: 231.924.6160

visit us at: www.mightylube.com