



MIGHTY LUBE SYSTEMATIC LUBRICATION, INC.

Fremont, Michigan

TECHNICAL DATA SHEET TYPE MX-HT LUBRICANT

Mighty Lube Type MX-HT Lubricant is a heavy duty, anti-wear lubricant, which has been formulated to withstand the most extreme industrial conveyor applications.

The use of Mighty Lube Systematic Lubrication will result in a conveyor system that is protected against wear and corrosion over temperature range exceeding 450°F with limited protection up to 1200°F.

Mighty Lube Type MX-HT Lubricant is a result of specialty chemicals being formulated to exceed all the characteristics of an excellent lubricant. Type MX-HT Lubricant consists of a solvent which acts as a cleaner, penetrator and carrier providing a pathway for the other components to work their way into the wear points. Graphite and synthetic fluids act as the base for the lubricant. This provides a thin film with anti-wear, extreme pressure and temperature protection.

Mighty Lube Type MX-HT Lubricant and lubrication equipment are a result of years of development to produce a highly technical system that provides maximum protection against wear, corrosion, and to insure trouble free operation without waste and equipment down time.

TYPICAL SPECIFICATIONS:

Viscosity SUS @100°F.	45
Pour Point °F.	-55
Flash Point °F.	230
Color	Black
Viscosity Index	140
Solids Lubricant (suspension)	Graphite
Rust Preventive Properties (ASTM D665A) Test	No Corrosion
Copper Corrosion Test	No Corrosion

Mfg. by Mighty Lube Systematic Lubrication, Inc., Fremont, MI 49412
231-924-6160

9569 West 40th Street
Fremont, Michigan 49412

fax: 231.924.6810
email: info@mightylube.com

telephone: 231.924.6160

visit us at: www.mightylube.com