



MIGHTY LUBE SYSTEMATIC LUBRICATION, INC.

Fremont, Michigan

TECHNICAL DATA SHEET

TYPE SS-3 LUBRICANT

Mighty Lube Type SS-3 Lubricant is a thin film, anti-wear lubricant formulated to perform under the most demanding of conveyor applications.

Specifically formulated for the coating industry, Type SS-3 shows high lubricity and excellent paint and powder compatibility. Type SS-3's water dispersion qualities make it ideal on wash lines and other locations where moisture can be a problem. Mighty Lube Type SS-3 is indicated anywhere maximum chain life is desired at temperatures of up to 500+ degrees F.

Mighty Lube Type SS-3's base lubricants and anti-oxidants are suspended in a penetrating solvent that acts as both a cleaner and a carrier, penetrating to all vital wear points when properly applied by Mighty Lube Lubricating Equipment. The solvent then evaporates, leaving behind a thin film lubricant of the highest quality anti wear agents and rust inhibitors, protecting vital moving parts from wear and corrosion.

Mighty Lube Type SS-3 Lubricant and Mighty Lube Lubricating Equipment are the result of years of development dedicated to providing industry with the highest quality systematic approach to protection against conveyor wear, corrosion, waste and downtime.

TYPICAL SPECIFICATIONS:

| | |
|------------------------------|---|
| Kinematics Viscosity | 100°C=0.70 cSt 40°C=1.86 cSt |
| Rust Characteristics (D665A) | Rating A, No Rust Detected |
| Flash Point °F. (D92) | 145°F |
| Four Ball Wear Scar (D4172) | 0.33 mm |
| Four Ball EP (D27830) | Load Wear Index 94.25 kg Weld Point 250 kg |

Mfg. by Mighty Lube Systematic Lubrication, Inc., Fremont, MI 49412
231-924-6160

9569 West 40th Street
Fremont, Michigan 49412

fax: 231.924.6810
email: info@mightylube.com

telephone: 231.924.6160

visit us at: www.mightylube.com