

MODEL #OP-08

OPCO® Power Brush Cleaning System Conveyor Chain & Trolley Wheel Cleaner

The OP-08 powered brush assembly reduces downtime while it cleans your conveyor system. It is designed to clean the conveyor chain, trolley wheels and trolley brackets. This unit fits overhead monorail or power & free conveyors.

FEATURES/BENEFITS

- Automatically cleans while conveyor is in operation
- Eliminates expensive, time-consuming manual cleaning
- Removes dirt, rust, scale, paint, and/or chemical residue
- Brushes shaped for your conveyor, for efficient operation
- Brush tension can be adjusted while conveyor is running
- Reduces drag on drive motors, extending life
- Provides proper grounding for electrostatic finishing
- Plated hardware provides longer component life
- Fits overhead, inverted and floor conveyors



OPTIONAL EQUIPMENT

- 575V, 50/60Hz motors available
- Electric timer for automatically starting and stopping cleaner action at any desired intervals
- Air valve to blow off particles lying on chain parts
- Explosion-proof motor and fiber brushes for hazardous areas
- Metal shroud enclosure available with or without vacuums
- Other brush materials available
- Motor starter
- Other voltages available
- Reversing Motor starter with time delay



MIGHTY LUBE®
Systematic Lubrication, Inc.

WWW.MIGHTYLUBE.COM

9569 WEST 40TH STREET • FREMONT, MICHIGAN 49412
PHONE 231-924-6160 | FAX 231-924-6810
EMAIL info@mightylube.com



MODEL #OP-08

OPCO® Power Brush Cleaning System Conveyor Chain & Trolley Wheel Cleaner

TECHNICAL ASSISTANCE

Customized technical assistance programs are available.

WARRANTY

A limited warranty is provided with each OP-08 Cleaner.

WEARMASTER LUBRICANTS

Using the right lubricant for the application can save you money otherwise lost to wear, increased power consumption and unscheduled downtime.

Recognized worldwide as lubrication systems specialists, we have years of experience in every aspect of conveyor lubrication – from equipment design, sales and installation to lubricant sales, systems service, consultation and custom problem solving. As a result, we are familiar with your needs and concerns. We can supply you with the WearMaster lubricants that will provide the best results in your conveyor system.

SPECIFICATIONS

| | |
|-------------------|---|
| MOTOR | 2 hp, 208-220/440-480 V, 60 cycle, 3 phase |
| BEARINGS | Heavy duty, shielded and sealed, self aligning |
| HOUSING | Thick-walled cast aluminum for greater strength |
| SHAFTING | 1 in diameter steel handles max loads |
| BRUSHES | Crimped steel |
| GUARDS | Neoprene rubber curtains surround brushes |
| DIMENSIONS | 24 in W x 24 in D x 32.5 in H |



MIGHTY LUBE®
Systematic Lubrication, Inc.

WWW.MIGHTYLUBE.COM

9569 WEST 40TH STREET • FREMONT, MICHIGAN 49412
PHONE 231-924-6160 | FAX 231-924-6810
EMAIL info@mightylube.com